Miele







PRI 217 | 65 in. wide roller

Features

- State-of-the-art controls: Touch display
- Flexibly positioned heater plate for perfect rotary ironing performance
- Durable long-lasting roller cover
- · Convenient return feed
- Variable roller speed
- Finger guard for ultimate safety
- 20,000 hours of operation



Perfect Laundry Finish

Uniform pressure over the entire working width guarantees a perfect laundry finish.



FlexControl Foot Switch

Feed in items flawlessly by activating the FlexControl foot pedal switch that can be positioned where needed.



Easy and Convenient Operation

A large touch display is used to easily and precisely select settings such as temperature and rotational speed.



Easy Cleaning and Care of the Heater Plate

Consistent finish quality thanks to notification when the ironer requires cleaning and waxing.

Mat. No.	Model	Heat Type	Electrical	Finish
11744790	PRI 217	Electric	240V / 50-60 Hz / 3 Ph, 3 x 50 A	Iron-Grey



Heated Type (EL) Electric Roller diameter 913/16 (250 mm) Working width 653/8 (1,660 mm) Heater plate material Aluminum Throughput at 25% residual moisture (kg/h) 50 Width 881/8 in. (2,238 mm) Depth 253/16 in. (650 mm) Height 4311/16 in. (1,110 mm) Weight 417 lbs. (189 kg) Shipping Width 941/2 in. (2,400 mm) Shipping Depth 337/8 in. (860 mm) Shipping Height 5511/16 in. (1,414 mm) Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min. 1.5
Roller diameter 9 13/16 (250 mm) Working width 65 3/8 (1,660 mm) Heater plate material Aluminum Throughput at 25% residual moisture (kg/h) 50 Width 88 1/8 in. (2,238 mm) Depth 25 9/16 in. (650 mm) Height 43 11/16 in. (1,110 mm) Weight 417 lbs. (189 kg) Shipping Width 94 1/2 in. (2,400 mm) Shipping Depth 33 7/8 in. (860 mm) Shipping Height 55 11/16 in. (1,414 mm) Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min. 1.5
Heater plate material Throughput at 25% residual moisture (kg/h) Width B8 1/8 in. (2,238 mm) Depth 25 9/16 in. (650 mm) Height 43 11/16 in. (1,110 mm) Weight Shipping Width 94 1/2 in. (2,400 mm) Shipping Depth 33 7/8 in. (860 mm) Shipping Height 55 11/16 in. (1,414 mm) Shipping Weight Minimum ironer speed, can be set in ft/min. 1.5
Throughput at 25% residual moisture (kg/h) Width 881/8 in. (2,238 mm) Depth 25 9/16 in. (650 mm) Height 43 11/16 in. (1,110 mm) Weight 417 lbs. (189 kg) Shipping Width 94 1/2 in. (2,400 mm) Shipping Depth 33 7/8 in. (860 mm) Shipping Height 55 11/16 in. (1,414 mm) Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min.
Width 88 ½8 in. (2,238 mm) Depth 25 ½16 in. (650 mm) Height 43 ½1 in. (1,110 mm) Weight 417 lbs. (189 kg) Shipping Width 94 ½ in. (2,400 mm) Shipping Depth 33 ½8 in. (860 mm) Shipping Height 55 ½1 in. (1,414 mm) Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min. 1.5
Depth 25 9/16 in. (650 mm) Height 43 11/16 in. (1,110 mm) Weight 417 lbs. (189 kg) Shipping Width 94 1/2 in. (2,400 mm) Shipping Depth 33 7/8 in. (860 mm) Shipping Height 55 11/16 in. (1,414 mm) Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min. 1.5
Depth 25 9/16 in. (650 mm) Height 43 11/16 in. (1,110 mm) Weight 417 lbs. (189 kg) Shipping Width 94 1/2 in. (2,400 mm) Shipping Depth 33 7/8 in. (860 mm) Shipping Height 55 11/16 in. (1,414 mm) Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min. 1.5
Height 43 ^{11/16} in. (1,110 mm) Weight 417 lbs. (189 kg) Shipping Width 94 ^{1/2} in. (2,400 mm) Shipping Depth 33 ^{7/8} in. (860 mm) Shipping Height 55 ^{11/16} in. (1,414 mm) Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min. 1.5
Weight 417 lbs. (189 kg) Shipping Width 94 \(^{1/2}\) in. (2,400 mm) Shipping Depth 33 \(^{7/8}\) in. (860 mm) Shipping Height 55 \(^{11/16}\) in. (1,414 mm) Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min. 1.5
Shipping Width 94 \(^{1/2}\) in. (2,400 mm) Shipping Depth 33 \(^{7/8}\) in. (860 mm) Shipping Height 55 \(^{11/16}\) in. (1,414 mm) Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min. 1.5
Shipping Depth 33 T/8 in. (860 mm) Shipping Height 55 T1/16 in. (1,414 mm) Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min. 1.5
Shipping Depth 33 T/8 in. (860 mm) Shipping Height 55 T1/16 in. (1,414 mm) Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min. 1.5
Shipping Height 55 11/16 in. (1,414 mm) Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min. 1.5
Shipping Weight 472 lbs. (214 kg) Minimum ironer speed, can be set in ft/min. 1.5
Minimum ironer speed, can be set in ft/min. 1.5
NACTOR OF THE CONTRACT OF THE
Maximum ironer speed, can be set in ft/min. 4.5
Standard electrical connection 240 V, 50-60 Hz, 3 Ph
Possible voltage variant 1 220 V, 50-60 Hz, 3 Ph
Possible voltage variant 2 208 V, 50-60 Hz, 3 Ph
Heating Power 12.4 kW
Fuse 3 x 50 A



Miele APRI 319 Trough Cleaning Set

APRI 319 Ironer cleaner starter package with cleaning cloth, waxing cloth and wax.

Article number 59530319EU / Material number 11923830



5610 McAdam Road, Mississauga, Ontario L4Z 1P1 905.890.1220 • 800.387.9503 • Fax: 905.890.7039 email: harco@harcoco.com • www.harcoco.com

in linkedin.com/company/miele-professional



