



Maximum Performance



# MID-PERFORMANCE RANGE

UNIMAC.COM

UW45 - UW130 POCKET HARDMOUNT WASHER-EXTRACTORS

# PRICED TO PERFORM.

As the leading manufacturer of on-premises laundry equipment, UniMac® offers more than seven decades of incomparable quality and long-lasting performance. Our UW series is built with unyielding construction to ensure industrial strength. Our cutting-edge innovations and technologies reduce costs and maximize throughput. And we're constantly improving. It's all part of our commitment to providing the lowest cost of ownership in the industry.

UniMac's Mid-Performance range of UW washer-extractors has all the hallmarks of the brand's legendary durability, and are designed for laundries requiring less robust feature sets – that means you get exceptional value for your money. Offered in 45- through 130-pound capacity models, the UW Mid-Performance line is engineered to deliver excellent wash results without sacrificing quality.

A ten-year warranty protects bearings, seals, frame, and cylinder shaft assembly from failure or breakage during normal operation due to defects in material or workmanship. A limited three-year warranty is offered on all other parts.



# UW SERIES – AT A GLANCE.



**EXCELLENT VALUE  
FOR YOUR DOLLAR**



**INDUSTRY-LEADING  
QUALITY BACKED WITH  
PEACE OF MIND**



**ROBOTICALLY  
WELDED FRAME**



**AUTO LEAK  
DETECTION**

- Industrial construction is built to run 24/7
- Helps reduce drying time and increase throughput with a 200 g-force extraction
- Bigger motor has 67% more horsepower than cabinet washer-extractors
- Handles unbalanced loads effortlessly
- UW 45/65 is 34.12" wide and easily fits through 36" commercial doorways
- 30 Programmable cycles
- Perforated cylinder ribs maximize wash action
- Auto leak detection greatly reduces water loss due to valve blockages or failures
- Simple installation with vertical access to frame bolts



Proudly based in Ripon, Wisconsin, USA, UniMac is dedicated to research, development and testing to provide equipment that delivers industrial strength and long-lasting quality. Our products undergo a 5-stage product development process and are pushed beyond their limits in our state-of-the-art test lab to ensure they exceed the toughest demands of the commercial environment and meet our customers' highest standards.

# UW HARDMOUNT WASHER-EXTRACTORS 45-130LB

SPECIFICATIONS		UW45		UW65		UW85	UW105	UW130
Capacity - lb (kg)		45 (20.4)		65 (30)		85 (38.5)	105 (47.6)	130 (60)
Cylinder Diameter - in (mm)		31 (787)		31 (787)		36 (914)	36 (914)	42 (1067)
Cylinder Depth - in (mm)		16.6 (422)		22.1 (561)		22 (559)	27 (686)	24½ (630)
Cylinder Volume - cu ft (liters)		7.3 (207)		9.7 (275)		13 (368)	15.9 (450)	19.6 (555)
Width - in (mm)		34.1 (866)		34.1 (866)		40.1 (1019)	40.1 (1019)	46.1 (1171)
Depth - in (mm)		45.3 (1151)		51.1 (1298)		51.2 (1300)	56.2 (1427)	54.5 (1384)
Height - in (mm)		64.7 (1643)		64.7 (1643)		67.6 (1717)	67.6 (1717)	72.6 (1844)
Door Opening Size - in (mm)		17.8 (452)		17.8 (452)		21 (533)	21 (533)	24 <sup>1</sup> / <sub>16</sub> (630)
Door Bottom to Floor - in (mm)		28.08 (713.23)		28.08 (713.23)		28.8 (732)	28.8 (732)	30.5 (775)
Motor Size - HP (kW)		5 (3.7)		5 (3.7)		7.5 (5.6)	7.5 (5.6)	10 (7.5)
Control Options		M30		M30		M30	M30	M30
Total # of Speeds		L Sp	M Sp	L Sp	M Sp	M Sp	M Sp	M Sp
		5	6	5	6	7	7	7
Cylinder Speed RPM ( G-Force)	Gentle	30 (0.4)	30 (0.4)	30 (0.4)	30 (0.4)	28 (.40)	28 (.40)	26 (.40)
	Wash	42 (0.78)	42 (0.78)	42 (0.78)	42 (0.78)	39 (.78)	39 (.78)	36 (.77)
	Distribution	75 (2.5)	75 (2.5)	75 (2.5)	75 (2.5)	70 (2.5)	70 (2.5)	65 (2.5)
	Very Low Extract	248 (27)	248 (27)	248 (27)	248 (27)	230 (27)	230 (27)	213 (27)
	Low Extract	477 (100)	477 (100)	477 (100)	477 (100)	443 (100)	443 (100)	410 (100)
	Medium	-	674 (200)	-	674 (200)	542 (150)	542 (150)	502 (150)
	High	-	-	-	-	626 (200)	626 (200)	579 (200)
Drain Diameter - in (mm)		3 (76)		3 (76)		3 (76)	3 (76)	3 (76)
Steam Connection - in (mm)		½ (13)		½ (13)		½ (13)	½ (13)	¾ (19)
Water Inlet Connection - in (mm)		2 @ ¾ (19)		2 @ ¾ (19)		2 @ ¾ (19)	2 @ ¾ (19)	2 @ 1 (25)
Shipping Dimensions - in (mm)	Width	37.2 (945)		37.2 (945)		43.2 (1097)	43.2 (1097)	49.2 (1250)
	Depth	53.8 (1367)		53.8 (1367)		61.8 (1570)	61.8 (1570)	64.8 (1646)
	Height	65 (1651)		65 (1651)		69.4 (1763)	69.4 (1763)	76.4 (1941)
Net Weight - lb (kg)		1080 (490)		1110 (503)		1670 (757)	1700 (771)	2040 (925)
Standard Shipping Weight - lb (kg)		1120 (508)		1150 (522)		1720 (780)	1750 (794)	2100 (953)
Slat Crate Shipping Weight - lb (kg)		1250 (567)		1280 (581)		1870 (848)	1900 (862)	2260 (1025)
Agency Approvals		cULus		cULus		cULus	cULus	cULus

**TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM  
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458**

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.



**Chef de file en équipements de buanderie**

6565 Rue Abrams, Ville St. Laurent , QC H4S 1X9  
Phone: 1-888-427-2626 • Fax: 1-514-331-0800  
email: info@harcoinc.ca • www.harcoinc.com