



COLLAR AND CUFF PRESSES



WWW.PONY-USA.COM



PONY USA
FINISHING FIRST

Shirt presses line

This new line of presses perfectly combines with Pony shirt finishers. They guarantee impeccable finishing thanks to their powerful squeezing pressure and excellent heat distribution on their bucks. Our customers can choose the press that most suits their needs based on the dimensions, productivity and operation type (steam or electric).

All presses are equipped with powerful vacuum units to allow placing the garments and quickly remove any residual moisture. Additionally, they offer ergonomic solutions that allow operators to work with the proper posture, without getting tired up. The collar-and-cuff range features the Pony NO-SHINE Technology and includes the **CCP**, **DOUBLE** and **QUAD** models.

TECHNICAL DATA	CCP	DOUBLE	QUAD
REQUIRED POWER	110V/1/60 Hz	110/1/60 Hz	230/3/60Hz
VACUUM MOTOR	0,37 kW	0,37 kW	0,55 kW
STEAM INLET	1/2"	1/2"	1/2"
RETURN OUTLET	1/2"	2 x 1/2"	1/2"
STEAM WORKING PRESSURE	72 ÷ 100 psi	72 ÷ 100 psi	72 ÷ 100 psi
STEAM CONSUMPTION	26 ÷ 33 Lbs/h	29 ÷ 33 Lbs/h	33 ÷ 39 Lbs/h
AIR SUPPLY	3/8"	3/8"	1/4"
STEAM WORKING PRESSURE	72 - 100 psi	72 ÷ 100psi	72 ÷ 100psi
AIR WORKING PRESSURE	86 ÷ 101,5 psi	87 ÷ 101,5 psi	87 ÷ 101,5 psi
AIR CONSUMPTION	1.65 cubic feet/ cycle	1.65 cubic feet/ cycle	1.75 cubic feet/ cycle
OVERALL DIMENSIONS	44 x 45 in	44 x 45 in	52,5 x 52 x 65 in
NET WEIGHT	631 Lbs	644 Lbs	992 Lbs
GROSS WEIGHT (INDUPACK)	670 Lbs	683 Lbs	1080 Lbs
PACKAGING DIMENSIONS	53 x 45 x 57 in	54 x 45 x 57 in	48 x 53 x 79 in

CCP

Collar-and-cuff press with Teflon-coated upper buck and lower buck with vacuum and Nomex® pad. Both bucks are steam-heated. Twin-button head closing system with safety devices. Productivity: up to 80 shirts per hour.

DOUBLE

The double buck of this press allows to finish TWO collars and FOUR cuffs at the same time. The upper head is Teflon-coated while the lower buck has vacuum and Nomex® cover. They are both steam-heated. Productivity: up to 180 shirts per hour.

QUAD

This compact-designed quadruple rotary press has a modular framework that eases transport and passage even in tight spaces which allows for a quick installation. Quad features two steam-heated rotary lower bucks with Nomex® cover, both with vacuum, and a fixed steam-heated and Teflon-coated upper head. PLC touch-screen controls. No access to the danger area during operation. Productivity: up to 240 shirts per hour.



5610 McAdam Road, Mississauga, Ontario L4Z 1P1
905.890.1220 • 800.387.9503 • Fax: 905.890.7039
email: harco@harcoco.com • www.harcoco.com